

Gateway endpoints

What the Gateway exposes, for when you are integrating something yourself rather than using the Endpoint Suite.

Chat endpoints

Path	Shape
POST /v1/messages	Anthropic — Claude Code
POST /v1/chat/completions	OpenAI — Cursor, Copilot
POST /azure/openai/deployments/{deployment}/chat/completions	Azure OpenAI
POST /gemini/v1beta/models/{model}	Gemini

They mirror the upstream providers' own shapes, which is what makes governing existing tools possible without modifying them.

Supporting endpoints

- GET /v1/models — an OpenAI-compatible model list. VS Code Copilot's custom-endpoint feature probes this to populate its dropdown. It is a curated list, not a statement of what your organization is entitled to.
- GET /v1/status — per-provider health.
- GET /healthz — public liveness.

MCP endpoints

- POST /mcp/{alias} — a routed remote MCP server, registered on MCP Inventory.
- POST /mcp/decide — the policy decision the Endpoint Suite's shim asks for.
- POST /mcp/observations — the shim reporting observed tool schemas and protocol versions.

The public Observatory

GET /v1/slopsquat/observatory needs no authentication. It returns the anonymized feed of commonly hallucinated package names. Use it in your own supply-chain checks if it is useful.

Two ways to authenticate

A normal `Authorization: Bearer` or `x-api-key` header, **or** a device token embedded in the path. The Endpoint Suite uses the second form, because it can be written into a tool's base URL setting where there is nowhere to put a header.

Revision #5

Created 2026-08-02 10:19:30 UTC by Sentilai Docs

Updated 2026-08-02 16:28:22 UTC by Sentilai Docs